

Material: ANSI/AA AZ81

Specification Standards for Die Castings

Group: Non-Ferrous Magnesium Alloy Sub

Group: ANSI/AA for Die Castings

Application: Intended for Valve, Pump, General Engineering, Automotive and Other Industries Grade

Belongs to the Industry: Casting

Chemical Composition			Heat Treatment	
Aluminium	Al %	7.000 - 8.500	As-Cast	
Zinc	Zn %	0.300 - 1.000		
Manganese	Mn %	0.170 min.		
Silicon	Si %	0.050 max.		
Iron	Fe %	0.004 max.		
Copper	Cu %	0.015 max.		
Nickel	Ni %	0.001 max.		
Other	Ot%	0.010 max.		
Magnesium	Mg %	Balance		
-	-	-	Mechanical Properties	
-	-	-		
-	-	-		
-	-	-		
-	-	-		
-	-	-		
-	-	-		
			Tensile Strength in Mpa	220 min.
			Yield Strength in Mpa	150 min.
			Elongation in %	3 min.
			Reduction of Area in %	-
			Hardness in BHN	72 min.
			Impact in Joule	-

Cross Reference Table			
Material	Standard	Country	Grade Belong to the Industry
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-

Disclaimer: All information displayed in our data sheets are for reference purpose only and are sole property of their respective owners. Information and or material are used for educational purposes only. Data at actual may vary at actual and case to case basis. ICAST Alloys LLP does not guarantee validity of these parameters. Warranties and liabilities are exclusive to our terms and conditions of business.

Customer Care: +91-99090 45075 Email: info@icastllp.com