

Material: ASME A731 TP XM-33

Standard Specification for Castings, Seamless and Welded Ferritic Stainless Steel Pipe

Group: Ferrous Stainless Steel Alloys

Sub Group: ASME A731 TP XM-33 Seamless and Ferritic Stainless Steel Pipe

Application: Intended for Valve, Pump, General Engineering, Automotive and Other Industries

Grade Belongs to the Industry: Pipe

Chemical Composition			Heat Treatment	
Carbon	C %	0.060 max.	Normalizing or Annealing or Hardening + Tempering	
Silicon	Si %	0.750 max.		
Manganese	Mn %	0.750 max.		
Phosphorus	P %	0.040 max.		
Sulphur	S %	0.020 max.		
Chromium	Cr %	25.000 - 27.000		
Molybdenum	Mo %	0.750 - 1.500		
Copper	Cu %	0.200 max.		
Nitrogen	N %	0.040 max.		
Titanium	Ti %	0.200 - 1.000		
Ni+Cu	Ni% + Cu%	0.500 max.	Mechanical Properties	
Iron	Fe %	Balance	Tensile Strength in Mpa	450 min.
-	-	-	Yield Strength in Mpa	275 min.
-	-	-	Elongation in %	20 min.
-	-	-	Reduction of Area in %	-
-	-	-	Hardness in BHN	-
-	-	-	Impact in Joule	-

Cross Reference Table			
Material	Standard	Country	Grade Belong to the Industry
SA-731 TP XM-33	ASME	USA	Casting
A176 Type XM-27	ASTM	USA	Plate, Sheet and Strip
A240 Type XM-27	ASTM	USA	Plate, Sheet and Strip
A276 XM-27	ASTM	USA	Bar and Shapes
S44627	UNS	USA	Plate, Sheet and Strip
SM-27	SAE	USA	Plate, Sheet and Strip
SA-276 XM-27	ASME	USA	Bar and Shape

Disclaimer: All information displayed in our data sheets are for reference purpose only and are sole property of their respective owners. Information and or material are used for educational purposes only. Data at actual may vary at actual and case to case basis. ICAST Alloys LLP does not guarantee validity of these parameters. Warranties and liabilities are exclusive to our terms and conditions of business.

Customer Care: +91-99090 45075 Email: info@icastllp.com