

Material: ASME SB-150 C63020

Standard Specification for Aluminum Bronze Rod, Bar and Shapes

Group: Non-Ferrous Copper Alloy

Sub Group: ASME SB-150 Aluminum Bronze Rod, Bar and Shapes

Application: Intended for Valve, Pump, General Engineering, Automotive and Other Industries Grade

Belongs to the Industry: Rod, Bar and Shape

Chemical Composition			Heat Treatment	
Aluminium	Al %	10.000 - 11.000	Hardening and Tempering	
Cobalt	Co %	0.200 max.		
Chromium	Cr %	0.050 max.		
Iron	Fe %	4.000 - 5.500		
Manganese	Mn %	1.500 max.		
Ni + Co	Ni% + Co%	4.200 - 6.000		
Lead	Pb %	0.030 max.		
Tin	Sn %	0.250 max.		
Zinc	Zn %	0.300 max.		
Cu + Ag	Cu% + Ag%	74.500 min.		
-	-	-	Mechanical Properties Tensile Strength in Mpa 890 - 930 Yield Strength in Mpa 620 - 690 Elongation in % 6 min. Reduction of Area in % - Hardness in HRB 26 min. Impact in Joule -	
-	-	-		
-	-	-		
-	-	-		
-	-	-		
-	-	-		
-	-	-		

Cross Reference Table			
Material	Standard	Country	Grade Belong to the Industry
C63020	UNS	USA	Rod, Bar, Tube and Shapes
B150 C63020	ASTM	USA	Rod, Bar and Shape
4590	SAE	USA	Casting
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-

Disclaimer: **All information displayed in our data sheets are for reference purpose only and are sole property of their respective owners. Information and or material are used for educational purposes only. Data at actual may vary at actual and case to case basis. ICAST Alloys LLP does not guarantee validity of these parameters. Warranties and liabilities are exclusive to our terms and conditions of business.**

Customer Care: +91-99090 45075 Email: info@icastllp.com