

Material: ASTM B283 C67500

Standard Specification for Copper and Copper-Alloy Die Forgings

Group: Non-Ferrous Copper Alloy

Sub Group: ASTM B283 Copper and Copper-Alloy Die Forgings

Application: Intended for Valve, Pump, General Engineering, Automotive and Other Industries Grade

Belongs to the Industry: Forging

Chemical Composition			Heat Treatment	
Aluminium	Al %	0.250 max.	Normalizing or Annealing or Tempering	
Iron	Fe %	0.800 - 2.000		
Manganese	Mn %	0.050 - 0.500		
Lead	Pb %	0.200 max.		
Tin	Sn %	0.500 - 1.500		
Copper	Cu %	57.000 - 60.000		
Zinc	Zn %	Balance		
-	-	-	Mechanical Properties Tensile Strength in Mpa 495 min. Yield Strength in Mpa 235 min. Elongation in % 33 min. Reduction of Area in % - Hardness in HRB 69 min. Impact in Joule -	
-	-	-		
-	-	-		
-	-	-		
-	-	-		
-	-	-		
-	-	-		
-	-	-		
-	-	-		

Cross Reference Table			
Material	Standard	Country	Grade Belong to the Industry
B124 C67500	ASTM	USA	Rod, Bar and Shapes
B138 C67500	ASTM	USA	Rod, Bar and Shape
CA675	SAE	USA	Rod, Bar and Shape
F467 C67500	ASTM	USA	Nut
SB-283 C67500	ASME	USA	Forging
SF-467 C67500	ASME	USA	Nut
SF-468 C67500	ASME	USA	Bolts, Hex Cap Screws and Studs

Disclaimer: All information displayed in our data sheets are for reference purpose only and are sole property of their respective owners. Information and or material are used for educational purposes only. Data at actual may vary at actual and case to case basis. ICAST Alloys LLP does not guarantee validity of these parameters. Warranties and liabilities are exclusive to our terms and conditions of business.

Customer Care: +91-99090 45075 Email: info@icastllp.com



+91-99090 45075



info@icastllp.com



ICAST ALLOYS LLP, Plot 2527, Road H1, Kranti Gate, GIDC Metoda, Lodhika, Rajkot-360021, Gujarat, India