

Material: ASTM B283 C71520

Standard Specification for Copper and Copper-Alloy Die Forgings

Group: Non-Ferrous Copper Alloy

Sub Group: ASTM B283 Copper and Copper-Alloy Die Forgings

Application: Intended for Valve, Pump, General Engineering, Automotive and Other Industries Grade

Belongs to the Industry: Forging

Chemical Composition			Heat Treatment	
Carbon	C %	0.050 max.	Normalizing or Annealing or Tempering	
Iron	Fe %	0.400 - 1.000		
Manganese	Mn %	1.000 max.		
Ni + Co	Ni% + Co%	29.000 - 33.000		
Phosphorus	P %	0.020 max.		
Lead	Pb %	0.020 max.		
Sulphur	S %	0.020 max.		
Zinc	Zn %	0.500 max.		
Copper	Cu %	65.000 min.		
-	-	-	Mechanical Properties	
-	-	-	Tensile Strength in Mpa	310 - 380
-	-	-	Yield Strength in Mpa	124 - 138
-	-	-	Elongation in %	30 - 45
-	-	-	Reduction of Area in %	-
-	-	-	Hardness in HRB	35 min.
-	-	-	Impact in Joule	-

Cross Reference Table			
Material	Standard	Country	Grade Belong to the Industry
B124 C71520	ASTM	USA	Rod, Bar and Shapes
B151 C71520	ASTM	USA	Rod and Bar
B171 C71520	ASTM	USA	Plate and Sheet
B466 C71520	ASTM	USA	Pipe and Tube
SB-151 C71520	ASME	USA	Rod and Bar
SB-171 C71520	ASME	USA	Plate and Sheet
SB-283 C71520	ASME	USA	Forging

Disclaimer: All information displayed in our data sheets are for reference purpose only and are sole property of their respective owners. Information and or material are used for educational purposes only. Data at actual may vary at actual and case to case basis. ICAST Alloys LLP does not guarantee validity of these parameters. Warranties and liabilities are exclusive to our terms and conditions of business.

Customer Care: +91-99090 45075 Email: info@icastllp.com