

Material: DIN SG-NiMo16Cr16Ti

Standard Specification for Nickel and Nickel Alloy Rod, Wire and Strips

Group: Non-Ferrous Nickel Alloys

Sub Group: DIN SG-NiMo16Cr16Ti Nickel and Nickel Alloy Rod, Wire and Strips

Application: Intended for Valve, Pump, General Engineering, Automotive and other Industries

Grade Belongs to the Industry: Rod, Wire and Strips

Chemical Composition			Heat Treatment	
Carbon	C %	0.015 max.	As-Cast or Annealing or Age Hardning	
Silicon	Si %	0.080 max.		
Manganese	Mn %	1.000 max.		
Chromium	Cr %	14.000 - 18.000		
Iron	Fe %	3.000 max.		
Molybdenum	Mo %	14.000 - 17.000		
sulphur	S %	0.015 max.		
Titanium	Ti %	0.200 - 0.700		
Other	Ot%	0.500 max.		
Ni + Co	Ni% + Co%	56.000 min.	Mechanical Properties	
-	-	-	Tensile Strength in Mpa	650 min.
-	-	-	Yield Strength in Mpa	300 min.
-	-	-	Elongation in %	25 min.
-	-	-	Reduction of Area in %	-
-	-	-	Hardness in BHN	-
-	-	-	Impact in Joule	60 @ RT

Cross Reference Table			
Material	Standard	Country	Grade Belong to the Industry
2.4611	DIN	Germany	Rod, Wire and Strips
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-

Disclaimer: All information displayed in our data sheets are for reference purpose only and are sole property of their respective owners. Information and or material are used for educational purposes only. Data at actual may vary at actual and case to case basis. ICAST Alloys LLP does not guarantee validity of these parameters. Warranties and liabilities are exclusive to our terms and conditions of business.

Customer Care: +91-99090 45075 Email: info@icastllp.com