

Material: DIN VDM alloy 602 CA

Standard Specification for Nickel and Nickel Alloy Strip and Sheet

Group: Non-Ferrous Nickel Alloys

Sub Group: DIN VDM alloy 602 CA Nickel and Nickel Alloy Strip and Sheet

Application: Intended for Valve, Pump, General Engineering, Automotive and other Industries

Grade Belongs to the Industry: Strip and Sheet

Chemical Composition			Heat Treatment	
Carbon	C %	0.150 - 0.250	As-Cast or Annealing or Age Hardning	
Silicon	Si %	0.500 max.		
Manganese	Mn %	0.500 max.		
Chromium	Cr %	24.000 - 26.000		
Aluminium	Al %	1.800 - 2.400		
Copper	Cu %	0.100 max.		
Iron	Fe %	8.000 - 11.000		
Phosphorus	P %	0.020 max.		
Sulphur	S %	0.010 max.		
Titanium	Ti %	0.100 - 0.200		
			Mechanical Properties	
Yttrium	Y %	0.050 - 0.120	Tensile Strength in Mpa	675 min.
Zirconium	Zr %	0.010 - 0.100	Yield Strength in Mpa	270 min.
Nickel	Ni %	Balance	Elongation in %	30 min.
-	-	-	Reduction of Area in %	-
-	-	-	Hardness in BHN	-
-	-	-	Impact in Joule	-

Cross Reference Table			
Material	Standard	Country	Grade Belong to the Industry
2.4633	DIN	Germany	Strip and Sheet
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-

Disclaimer: All information displayed in our data sheets are for reference purpose only and are sole property of their respective owners. Information and or material are used for educational purposes only. Data at actual may vary at actual and case to case basis. ICAST Alloys LLP does not guarantee validity of these parameters. Warranties and liabilities are exclusive to our terms and conditions of business.

Customer Care: +91-99090 45075 Email: info@icastllp.com