

## Material: IS 4899 Grade 10

### Standard Specification for Steel Castings for General Engineering Purposes

**Group:** Ferrous Stainless Steel Alloys

**Sub Group:** IS 4899 Grade 10 Steel Castings for General Engineering Purposes

**Application:** Intended for Valve, Pump, General Engineering, Automotive and Other Industries

**Grade Belongs to the Industry:** Casting

Chemical Composition			Heat Treatment	
Carbon	C %	0.060 max.	As Cast or Annealing or Normalizing or Hardening and Tempering	
Silicon	Si %	1.000 max.		
Manganese	Mn %	1.000 max.		
Phosphorus	P %	0.040 max.		
Sulphur	S %	0.030 max.		
Chromium	Cr %	11.500 - 14.000		
Nickel	Ni %	3.500 - 4.500		
Molybdenum	Mo %	0.400 - 1.000		
Iron	Fe %	Balance	Mechanical Properties	
-	-	-	Tensile Strength in Mpa	760 - 930
-	-	-	Yield Strength in Mpa	550 min.
-	-	-	Elongation in %	14 min.
-	-	-	Reduction of Area in %	35 min.
-	-	-	Hardness in BHN	-
-	-	-	Impact in Joule	-

Cross Reference Table			
Material	Standard	Country	Grade Belong to the Industry
425C12	BS	British	Casting
2074/H3D	AS	Australia	Casting
3444 Grade 24	IS	India	Casting
A 352 Grade CA6NM	ASTM	USA	Casting
A 352 J91540	ASTM	USA	Casting
SA-352 Grade CA6NM	ASME	USA	Casting
SCS 6	JIS	Japan	Casting

**Disclaimer:** All information displayed in our data sheets are for reference purpose only and are sole property of their respective owners. Information and or material are used for educational purposes only. Data at actual may vary at actual and case to case basis. ICAST Alloys LLP does not guarantee validity of these parameters. Warranties and liabilities are exclusive to our terms and conditions of business.

Customer Care: +91-99090 45075 Email: [info@icastllp.com](mailto:info@icastllp.com)