

Material: SAE D4018

Standard Specification For Spheoidal Graphiite Cast Irons Castings

Group: Ferrous SG Iron / Ductile Iron Alloys

Sub Group: SAE D4018 Spheoidal Graphite Cast Irons Castings

Application: Intended for Valve, Pump, General Engineering, Automotive and Other Industries

Grade Belongs to the Industry: *Casting*

Heat Treatment

Mechanical Properties	
Tensile Strength in Mpa	400 min.
Yield Strength in Mpa	250 min.
Elongation in %	18 min.
Reduction of Area in %	-
Hardness in BHN	143 - 170
Impact in Joule	120 J @ RT

Cross Reference Table			
Material	Standard	Country	Grade Belong to the Industry
JS 400-18	ISO	International	Casting
JS 400-18	AS	Australia	Casting
A 536 60-40-18	ASTM	USA	Casting
D400	SAE	USA	Casting
5.3105	EN	European Union	Casting
EN-GJS-400-18	UNE	Spain	Casting
SG 400 I 18	IS	India	Casting

Disclaimer: All information displayed in our data sheets are for reference purpose only and are sole property of their respective owners. Information and or material are used for educational purposes only. Data at actual may vary at actual and case to case basis. ICAST Alloys LLP does not guarantee validity of these parameters. Warranties and liabilities are exclusive to our terms and conditions of business.

Customer Care: +91-99090 45075 Email: info@icastllp.com