

Material: STAS 2 CuMoCrNi 250

Standard Specification for Chromium and Chromium-Nickel Stainless Steel Plate, Sheet and Strip for Pressure Vessels and for General Applications

Group: Ferrous Stainless Steel Alloys

Sub Group: STAS 2 CuMoCrNi 250 Chromium and Chromium-Nickel Stainless Steel for Pressure Vessels and for General Applications

Application: Intended for Valve, Pump, General Engineering, Automotive and Other Industries

Grade Belongs to the Industry: Steel

Chemical Composition			Heat Treatment	
Carbon	C %	0.020 max.	Solution Annealing	
Silicon	Si %	1.000 max.		
Manganese	Mn %	2.000 max.		
Phosphorus	P %	0.035 max.		
Sulphur	S %	0.025 max.		
Chromium	Cr %	19.000 - 22.000		
Molybdenum	Mo %	4.000 - 5.000		
Nickel	Ni %	24.000 - 27.000		
Copper	Cu %	1.000 - 2.000	Mechanical Properties	
Iron	Fe %	Balance	Tensile Strength in Mpa	490 min.
-	-	-	Yield Strength in Mpa	215 min.
-	-	-	Elongation in %	35 min.
-	-	-	Reduction of Area in %	40 min.
-	-	-	Hardness in HB	187 max.
-	-	-	Impact in Joule	-

Cross Reference Table			
Material	Standard	Country	Grade Belong to the Industry
A240 UNS N08904	ASTM	USA	Steel, Plate, Sheet and Strip
SUS 890L	JIS	Japan	Steel, Plate, Sheet and Strip
TU Z 1 NCDU 25 20 04	AFNOR NF	France	Steel and Tube
X1NiCrMoCu25 20 5	EN	European Union	Forging
X1NiCrMoCu25-20-5	UNI	Italy	Steel, Plate, Sheet and Strip
X1NiCrMoCu25 20 5	DIN	Germany	Rolling and Forging
STS 890L	KS	Korea	Steel, Plate, Sheet and Strip

Disclaimer: All information displayed in our data sheets are for reference purpose only and are sole property of their respective owners. Information and or material are used for educational purposes only. Data at actual may vary at actual and case to case basis. ICAST Alloys LLP does not guarantee validity of these parameters. Warranties and liabilities are exclusive to our terms and conditions of business.

Customer Care: +91-99090 45075 Email: info@icastllp.com