

## Material: ANSI/AA ZA-27

## **Specification Standards for Die Castings**

**Group:** Non-Ferrous Zinc Alloy Sub Group: ANSI/AA for Die Castings

Application: Intended for Valve, Pump, General Engineering, Automotive and Other Industries Grade

**Belongs to the Industry:** Casting

Chemical Composition			Heat Treatment	
Aluminium	Al %	25.000 - 28.000		
Magnesium	Mg %	0.010 - 0.020		
Copper	Cu %	2.000 - 2.500		
Iron	Fe %	0.075 max.	As-Cast or Aging	
Lead	Pb %	0.006 max.		
Cadmium	Cd %	0.006 max.		
Tin	Sn %	0.003 max.		
Zinc	Zn %	Balance		
-	-	-	Mechanical Properties	
-	-	-	Tensile Strength in Mpa	426 min.
-	-	-	Yield Strength in Mpa	359 - 379
-	-	-	Elongation in %	2.000 - 3.500
-	-	-	Reduction of Area in %	-
-	-		Hardness in HB	116 - 122
-	-	-	Impact in Joule	9 - 16

Cross Reference Table					
Material	Standard	Country	ry Grade Belong to the Industry		
B86 ZA27	ASTM	USA	Casting		
B240 ZA27	ASTM	USA	Ingot and Casting		
Z35841	UNS	USA	Casting		
ZP2720	ISO	International	Casting		
ZP27	ISO	International	Casting		
-	-	-	-		
-	-	-	-		

Disclaimer: All information displayed in our data sheets are for reference purpose only and are sole property of their respective owners. Information and or material are used for educational purposes only. Data at actual may vary at actual and case to case basis. ICAST Alloys LLP does not guarantee validity of these parameters. Warranties and liabilities are exclusive to our terms and conditions of business.

Customer Care: +91-99090 45075 Email: info@icastllp.com







