

Material: UNI G22Ni10

Standard Specification for Low Alloy Steel With Low Temperature Toughness for Castings **Subject to Pressure**

Group: Ferrous Mild Steel Alloys

Sub Group: UNI G22Ni10 Low Alloy Steel With Low Temperature Toughness for Castings Subject to Pressure

Application: Intended for Valve, Pump, General Engineering, Automotive and Other Industries

Grade Belongs to the Industry: Casting

Chemical Composition			Heat Treatment	
Carbon	C %	0.250 max.		
Silicon	Si %	0.600 max.		
Manganese	Mn %	0.800 max.		
Phosphorus	P %	0.035 max.	Normalizing + Tempering or F	lardening + Tempering
Sulphur	S %	0.035 max.		
Nickel	Ni %	2.000 - 3.000		
Iron	Fe %	Balance		
-	-	-		_
-	-	-	Mechanical Properties	
-	-	-	Tensile Strength in Mpa	440 min.
-	-	-	Yield Strength in Mpa	275 min.
-	-	-	Elongation in %	21 min.
-	-		Reduction of Area in %	-
-	-	-	Hardness in BHN	-
-	-	-	Impact in Joule	-

Cross Reference Table				
Material	Standard	Country	Grade Belong to the Industry	
SA-352 LC2	ASME	USA	Casting	
1.5635	DIN	Germany	Steel	
J22500	UNS	USA	Casting	
G9Ni10	AFNOR NF	France	Casting	
SCPL 21	JIS	Japan	Casting	
F.8373	UNE	Spain	Casting	
A352 LC2	ASTM	USA	Casting	

Disclaimer: All information displayed in our data sheets are for reference purpose only and are sole property of their respective owners. Information and or material are used for educational purposes only. Data at actual may vary at actual and case to case basis. ICAST Alloys LLP does not guarantee validity of these parameters. Warranties and liabilities are exclusive to our terms and conditions of business.

Customer Care: +91-99090 45075 Email: info@icastllp.com



